

# Dover Tubular

**Alloys, Inc.**

## SEAMLESS EXTRUDED ALUMINUM PIPE & SEAMLESS DRAWN TUBE 6061-T6

### PRODUCT SPECIFICATIONS:

- **PIPE:** ASTM/ASME B241,B221,B345, SAE AMS-QQ-A200
- **TUBE:** ASTM B210, SAE AMS-WWT-700/6, AMS 4082 & AMS 4083

### PRODUCT GRADE & TEMPER:

- **PIPE:** 6061-T6/E6061-T6511
- **TUBE:** 6061-T6

### ORIGIN & COMPLIANCE:

- **PIPE:** Import
- **TUBE:** Import, Domestic, DFARS



**MASTER DISTRIBUTOR OF  
STAINLESS STEEL SINCE 1983**

PHONE 800.338.1000

E-MAIL SALES@DOVERTUBULARALLOYS.COM

FAX 973.361.0708

### GRADE/TEMPER 6061-T6 SEAMLESS EXTRUDED PIPE:

NPS	SCH	WALL
1/2"	40	0.109"
1/2"	80	0.147"
3/4"	40	0.113"
3/4"	80	0.154"
1"	10	0.109"
1"	40	0.133"
1"	80	0.179"
1-1/4"	10	0.109"
1-1/4"	40	0.140"
1-1/4"	80	0.191"
1-1/2"	10	0.109"
1-1/2"	40	0.145"
1-1/2"	80	0.200"
2"	10	0.109"
2"	40	0.154"
2"	80	0.218"
2-1/2"	10	0.120"
2-1/2"	40	0.203"
2-1/2"	80	0.276"
3"	10	0.120"
3"	40	0.203"
3"	80	0.300"
3-1/2"	10	0.120"
3-1/2"	40	0.226"
3-1/2"	80	0.318"
4"	10	0.120"
4"	40	0.237"
4"	80	0.337"
5"	40	0.258"
5"	80	0.375"
6"	40	0.280"
6"	80	0.432"

### GRADE/TEMPER 6061-T6 SEAMLESS DRAWN TUBE:

1/4"	1"	2-1/4"
5/16"	1-1/8"	2-1/2"
3/8"	1-1/4"	2-3/4"
7/16"	1-3/8"	3"
1/2"	1-1/2"	3-1/4"
9/16"	1-5/8"	3-1/2"
5/8"	1-3/4"	4"
3/4"	1-7/8"	4-1/2"
7/8"	2"	5"

### WALL THICKNESSES:

0.028"	0.065"	0.125"
0.035"	0.083"	0.188"
0.049"	0.095"	0.250"
0.058"	0.120"	